

Data Sheet for Article: AC208081--

Modular enclosure 1 door IP55 H=2000 W=800 D=800 mm

sheet steel, RAL7035, without mounting plate, four-point rod lock with push-pull handle



Technical Data

Net width (mm)	800,00
Net height (mm)	2.000,00
Netto depth (mm)	800,00
Net weight (kg)	99,50
Min. ambient temperature (°C)	-10
Max. ambient temperature (°C)	60
IP Rating	IP55
Protection class	I
Material	sheetsteel
Colour	RAL 7035 (Light grey)
Width (mm)	800
Height (mm)	2000
Depth (mm)	800
Corpus wall thickness (mm)	1,50
Door wall thickness (mm)	2
Number of bottom plates	4
Load capacity per door (kg)	100

Technical Data - continued

Number of doors	1
Bottom plates width (mm)	630
Product category	Modular enclosure
Total Load Capacity (kg)	1500
Mounting Plate Load Capacity (kg)	1500
Power loss (W)	-1158,00

Article Table

DESCRIPTION	Order No.
Modular enclosure 1 door IP55 H=2000 W=800 D=800 mm sheet steel, RAL7035, without mounting plate, four-point rod lock with push-pull handle	AC208081
Optional Accessories	
LED lighth for EC, infra (not available in this country)	IU006519CZ
Side panels (pair) H=2000 D=800 mm sheet steel RAL7035	ACSW2008
Plinth side parts (pair) with corner parts D=800 H=100 mm preassembled, sheet steel RAL9005 (Jet black)	ACSOT081
Plinth front and rear part W=800 H=100 mm sheet steel PU=2 pieces, RAL9005 (Jet black)	ACSOB081
Plinth side parts (pair) with corner parts D=800 H=200 mm preassembled, sheet steel RAL9005 (Jet black)	ACSOT082
Plinth front and rear part W=800 H=200 mm sheet steel PU=2 pieces, RAL9005 (Jet black)	ACSOB082
Mounting plate H=2000mm W=800mm galvanized sheet steel	ACMP2008
Slide-in rails for mounting plates in 800 mm deep enclosures of series AC and KC, PU=1 pair	ACCLT800
Baying kit for inside and outside mounting with 4x baying brackets and mounting accessories	ACCCI060
Gasket tape made of Polyethylene PE-01, IP55	ACSPDG01
Eye bolts M12 for lifting of AC and KC enclosures PU=4 pieces	ACLE9301
Document pocket, self-adhesive and screwable, DIN A4	ASDRA400
Push-pull handle in black with spring adjustment without insert	ACLSC502

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Adapter for half cylinder locks DIN18252 for push-pull handles of enclosure series AC, KC, AT and KT	ASLS2100
Adapter plate push-button insert for AC/KC enclosures	ASLSSI537
Cage nuts M6 (PU=10 pcs.)	ACCNM615
Fillister head screws M6x16 according to ISO 7380 PU=10 pieces	ACCNK006
Cage nuts M8 (PU=10 pcs.)	ACCNM815
Fillister head screws M8x16 according to ISO 7380 PU=10 pieces	ACCNK008
DIN-rail low, unperforated, sendzimir zincd Price per piece	BK14004--B
DIN-rail low, perforated, sendzimir zincd Preis pro Stück	BK14005--A
DIN-rail high, unperforated, sendzimir zincd DIN-rail high, unperforated, sendzimir zincd	IL14035--A
DIN-rail high, Long Hole 18x6.3mm, sendzimir zincd Price per piece	IL14037
Key for 5mm double-bit insert PU=1 piece	DV903532