

Data Sheet for Article: BK080007--

Flush-mounted enclosure 3-rows, 54MW, IP40, transparent door

H=520 W=391 D=106mm, protection class 2, ABS, halogen free, RAL 9003



SCHRACK-Info

- Flush-mounted domestic consumer unit enclosures in ABS with transparent plastic doors
- Lock: push-button, a small cylinder can be installed
- Includes PE and N terminals
- Protection class II
- Halogen free according to RoHS
- Rated voltage 400VAC / In=63A
- Ambient temperature: -25° to +60°C
- Glow wire test: 650°C
- Recess depth: 68-70mm
- Degree of protection: IP40, Impact resistance: IK08
- RAL9010 pure white



Technical Data

Net width (mm)	391,00
----------------	--------

Technical Data - continued

Net height (mm)	520,00
Netto depth (mm)	106,00
Net weight (kg)	2,60
EAN	9004840782127
Power loss (W)	-45,00
Min. ambient temperature (°C)	-25
Max. ambient temperature (°C)	60
Door material	Plastic, transparent
Halogen-free	Yes
Rows	3
MW per row	18
IP Rating	IP40

Article Table

DESCRIPTION	Order No.
Flush-mounted enclosure 3-rows, 54MW, IP40, transparent door H=520 W=391 D=106mm, protection class 2, ABS, halogen free, RAL 9003	BK080007
Optional Accessories	
Round cylinder sash lock 2233 for TOPO BK0800 + BK0801 metal, 2x keys included	BK080096