

Data Sheet for Article: BK080206--

# Wall-mounted enclosure 1-row, 18MW, IP65, transparent door

halogen free, UV stabilized, 400VAC/1500VDC, plastic ASA



## SCHRACK-Info

- Wall-mounted enclosures with transparent door
- Lock: rotary knob, a small cylinder can be installed
- Includes PE and N terminals
- Protection class II
- Halogen-free according to RoHS
- UV stability and weather resistant
- Rated voltage 400VAC, 1500VDC / In=63A
- Ambient temperature: -25° to +60°C
- Glow wire test: 650°C
- Lock: RONIS small cylinder possible
- Material: ASA
- Degree of protection IP65
- RAL7035 light grey



## Technical Data

|                               |                        |
|-------------------------------|------------------------|
| Net width (mm)                | 428,00                 |
| Net height (mm)               | 259,00                 |
| Netto depth (mm)              | 144,00                 |
| Net weight (kg)               | 1,74                   |
| EAN                           | 9004840886313          |
| Power loss (W)                | -20,00                 |
| Min. ambient temperature (°C) | -25                    |
| Max. ambient temperature (°C) | 60                     |
| Door material                 | Plastic                |
| Halogen-free                  | Yes                    |
| Version                       | wall mounted with door |
| Rows                          | 1                      |
| MW per row                    | 18                     |
| IP Rating                     | IP65                   |
| Colour                        | RAL 7035 (Light grey)  |

## Article Table

| DESCRIPTION                                                                                                            | Order No. |
|------------------------------------------------------------------------------------------------------------------------|-----------|
| Wall-mounted enclosure 1-row, 18MW, IP65, transparent door<br>halogen free, UV stabilized, 400VAC/1500VDC, plastic ASA | BK080206  |
| <b>Optional Accessories</b>                                                                                            |           |
| Round cylinder sash lock 2233X for BK0802 (IP65)<br>metal, 1x key included                                             | BK080095  |