

Data Sheet for Article: BK090097--

Half cylinder lock for BK09, IP65



Technical Data

Net width (mm)	19,00
Net height (mm)	19,00
Netto depth (mm)	27,45
Net weight (kg)	0,03
EAN	9004840994179
Max. ambient temperature (°C)	40

Article Table

DESCRIPTION	Order No.
Half cylinder lock for BK09, IP65	BK090097
Optional Accessories	
Wall-mounting Distribution Board 1-row 18MW transparent IP65 UV stability and weather resistant, 1000VDC; Plastic material ABS, 1x18MW, H=288 W=432 D=160, 1x N+PE (22x16mm ²)	BK090202
Wall-mounting Distribution Board 2-row 36MW transparent IP65 UV stability and weather resistant, 1000VDC; Plastic material ABS, 2x18MW, H=464 W=432 D=160, 1x N+PE (22x16mm ²)	BK090204
Wall-mounting Distribution Board 3-row 54MW transparent IP65 UV stability and weather resistant, 1000VDC; Plastic material ABS, 3x18MW, H=638 W=432 D=160, 2x N+PE (22x16mm ²)	BK090206
Wall-mounting Distribution Board 4-row 72MW transparent IP65 UV stability and weather resistant, 1000VDC; Plastic material ABS, 4x18MW, H=878 W=432 D=160, 3x N+PE (22x16mm ²)	BK090208