

Data Sheet for Article: BK090208--

Wall-mounting Distribution Board 4-row 72MW transparent IP65

UV stability and weather resistant, 1000VDC; Plastic material ABS, 4x18MW, H=878
W=432 D=160, 3x N+PE (22x16mm²)



SCHRACK-Info

- Wall-mounted enclosures with 2 transparent doors inclusive UV-Protection
- Lock: Pressure-operated mechanism, a small cylinder can be installed
- Cable Entry by elastic rubber membranes
- Includes PE and N terminals
- Halogen-free plastic materials
- Protection class II
- UV stability and weather resistant

- Rated voltage 400VAC, 1000VDC
- Ambient temperature: -25° to +85°C
- Material: ABS
- Degree of protection IP65
- Resistance to impact: IK07
- RAL7035 light grey

Technical Data

Net width (mm)	432,00
Net height (mm)	878,00
Netto depth (mm)	160,00
Net weight (kg)	7,69
EAN	9004840934489
Power loss (W)	-35,00
Min. ambient temperature (°C)	-25
Max. ambient temperature (°C)	85

Article Table

DESCRIPTION	Order No.
Wall-mounting Distribution Board 4-row 72MW transparent IP65 UV stability and weather resistant, 1000VDC; Plastic material ABS, 4x18MW, H=878 W=432 D=160, 3x N+PE (22x16mm ²)	BK090208
Optional Accessories	
Half cylinder lock for BK09, IP65	BK090097