

Door metal perforated 80% DS/DSZ/ DSS(IP20) 45U, W=600, RAL7035



SCHRACK-Info

All Doors are constructed for installation to SCHRACK free-standing Data-enclosures DS and DSZ.

Doors can be installed in front as a replacement of the standard glass-door or in the rear instead of the rear-panel.

Installation of door in the rear enables easier and quicker access to the backside of installed components for repair, maintenance or exchange.

Glassdoors to be used if it is necessary to look at installed components.

Solid Metaldoors if no view inside the cabinet shall be possible, e.g. in public areas.

Perforated Metaldoors for enhanced passive cooling of the installed active equipment..

Double-wing doors are used in case of limited space for opening of doors.

- Material:
 - Steel
 - Door glass: safety hardened, thickness 4 mm
- Color: Lightgrey RAL 7035
- IP protection: IP20
- Comfort swinghandle prepared for halfcylinder-lock.
- Installation:
 - Front: Instead of standard glas-door
 - Rear: Instead of standard fullmetal rear-panel
- Hinges: 3 pcs. at 42U and 45U doors
- Hinging: Right. Quick and easy changing to hinging left.
- External hinge system allows up to 180 degree door opening angle.
- Supply includes all materials needed for installation in front or rear.

Technical Data

Net width (mm)	597,00
Net height (mm)	2.010,00
Netto depth (mm)	24,00
Net weight (kg)	16,40
Min. ambient temperature (°C)	0
Max. ambient temperature (°C)	40
Suitable for enclosure width (mm)	600
Suitable for HU	45U-2105mm
Colour	RAL 7035 (Light grey)

DESCRIPTION	Order No.
Door metal perforated 80% DS/DSZ/DSS(IP20) 45U,W=600,RAL7035	DSRT4561