

Data Sheet for Article: DTWE045445

Network Enclosure Wall S-RACK, W=540 H=240 D=450, 19", 4U

RAL7035 Light grey



SCHRACK-Info

Mainly used in offices and office-like environments, such as flats, single-family homes, etc. Suitable as a central distributor in small to medium-sized network installations, but also for use as a floor distributor (sub-distributor) in the horizontal area of structured cabling. The removable side panels allow convenient access to the installed components, even afterwards. For active cooling of the built-in components, optional DTLT fan units with one or two fans can be mounted in the roof.

- **Material:** Powder-coated steel sheet housing
- **Material thickness:**
 - Top and bottom chassis: 1.0mm
 - Corner profile: 1.0mm
 - Rails: 1.5mm
 - Front door (glass): 4.0mm
 - Rear panel: 1.0mm
 - Side panel: 0.8mm
- **Colour:**
 - RAL7035 (light grey)
 - Corner profile and rear panel: RAL5005 (signal blue)
- **Height:** 4U
- **Maximum load:** With even distribution: 80kg
- **Degree of protection:** IP20

- **Doors:** Glass door of safety glass 4mm including lock and 2 keys. Door hinged on the right. Conversion to left hinged possible. Opening angle of the door: approx. 200°.
- **Side panels:** removable and lockable
- **Rails:** 19" rails (2 pieces) in the front of the cabinet, galvanised, depth-adjustable
- **Cable entry options:** in roof and floor
 - The floor is provided with a plastic blank cover.
 - The roof is equipped with a brush entry.
- **Cooling:**
 - Passive cooling through ventilation slots and heat exchange with the outside area.
 - Active cooling by optional DTLT fans, which are easily and quickly inserted into the

Technical Data

Net width (mm)	540,00
Net height (mm)	240,00
Netto depth (mm)	450,00
Net weight (kg)	9,40
EAN	9004840880700
Min. ambient temperature (°C)	5
Max. ambient temperature (°C)	40
HU	4
Colour	RAL 7035 / RAL 5005 (light grey / blue)
IP Rating	IP20
Max. load (kg)	80
Series	S-RACK

Article Table

DESCRIPTION	Order No.
Network Enclosure Wall S-RACK, W=540 H=240 D=450, 19", 4U RAL7035 Light grey	DTWE045445
Optional Accessories	
Roof Fan-unit 2 fan for S-RACK, analog thermostat, RAL7035 Lightgrey, Installation from outside of enclosure, for freestanding and wallmount enclosures	DTLTR02A
Roof Fan-unit 2 fans for S-RACK, switch (on/off), RAL7035 Light grey, Installation from outside of enclosure, for freestanding and wallmount enclosures	DTLTR02S
Roof Fan-unit 1 fan for S-RACK, analog thermostat, RAL7035 Lightgrey, Installation from outside of enclosure, for freestanding and wallmount enclosures	DTLTR01A
Roof Fan-unit 1 fan for S-RACK, switch (on/off), RAL7035 Light grey, Installation from outside of enclosure, for freestanding and wallmount enclosures	DTLTR01S

Article Table

DESCRIPTION	Order No.
Optional Accessories	
19" Shelf Fix, 1U, up to 30kg Load, D=300mm, Low Profile 2 Point Fixing, RAL7035	DTFT1300
Patchpanel 19" empty for 24 modules (SFA)(SFB), 1U, RAL7035 Light grey, patchcord lock down	HSE0240GS
19" Cable management panel, 1U, 5 metal rings 63mm, RAL7035	DTBC105R
19" Mounting set M6, 20 piece screw, nut, washer	DTSRA020
Switch 24xRJ45 10/100/1000, Silent, w/o fan, internal PSU Metal-Chassis, 19"	QLGSW2457
19" PDU, 9xSchuko, Profile ALU 1U, 2m-cable, RAL7035	IU070114
19" PDU, 7xSchuko with overvoltage protection, PVC, 1.25U 2m-connector cable, RAL7035	IU070113
19" PDU, 9x Schuko, switch, 1U, 2m-cable, Black, ALU ALU Profil	Q7070114-A
19" PDU, 7x Schuko, Switch, Overvoltage protection, 1U 2m-cable, Black, ALU	Q7070113-A