

Data Sheet for Article: DV900330-A

Light unit, Installation on 19"-rails, by magnet or screwing



Product Details

Key-Features

- Lighting for Racks and Industry
- Compact-Lighting 26 mm wide
- Rotor with fastening units
- To fix with and always without tools
- Magnet is always used for fastening
- With fix mounted connection cable
- On metal, on profiles, into the 19" -rack
- Fastening by magnet, fastening by magnet and screw, fastening by magnet and snap in
- Screw on profiles have variable hole distance
- Worldwide usage: power supply unit 230VAC/50-60 Hz
- CE, ENEC, TÜV-GS
- With door switch connection (optional)

Technical Data

Net width (mm)	483,00
Net height (mm)	25,00
Netto depth (mm)	55,00
Net weight (kg)	0,40

Technical Data - continued

Min. ambient temperature (°C)	-15
Max. ambient temperature (°C)	45

Datei Tabelle: Light unit, Installation on 19"-rails, by magnet or screwing

Electrical Parameter	
Lamp nominal wattage	8W
Rated voltage/frequency	230 V AC $\pm$ 10% / 50-60 Hz
Rated current 110 V AC/230 V AC	50 Hz - 0,030 A 60 Hz - 0,035 A
Connector door switch	2-pole mini-connector 2,5 A
Connection	2x0,75 mm ² , 1,5 mwiring colour: black
Protection type/-class	
Protection type/-class	IP 20/11
Light bulb	
Socket	T5/G5
Lamp start	Warm start
Service Life	10.000 h
Light colour	4.300 K (cold white)
Norms and certifications	
Labeling	CE, ENEC
Testing standards	EN 60598EN 55 015
Interference emissions	EN 61000-6-3
Interference immunity	EN 61000-6-2
Directives	73/23/EWG, 89/336/EWG, 2000/55/EG
more Informations	
operating device	electronic
length, height, wide	448 x 54,5x 26 mm
weight	approx. 400 gr.
working temperature	-15° to + 45 C°
store temperature	-20 to +85 C°
Humidity at work / Humidity at store	0-50% / 0-85%

Article Table

DESCRIPTION	Order No.
Light unit, Installation on 19"-rails, by magnet or screwing	DV900330-A
Optional Accessories	
Cable for doorswitch in DS/DSZ/DSS-enclosures	DV900332
Adapter for DS-, DSZ-, DSS-Enclosure and doorswitch ACDSW010	DSADA001
Door switch plastic IP65	ACDSW010