

Data Sheet for Article: DV900336-A

Light unit LED, 945lm, Installation on 19", magnet or screwing



Product Details

Key-Features

- Lighting for racks and industry
- Compact-lighting 26 mm wide
- Rotor with fastening units
- To fix with and always without tools
- Magnet is always used for fastening
- Effekitive LED-lighting, rotating LED-unit, life cycle 50.000 h
- With fix mounted connection cable
- On metal, on profile, into the 19" -rack
- Fastening by magnet, fastening by magnet and screw, fastening by magnet and snap in
- Screw on profiles have variable hole distance
- Power supply voltage: 230 V / 50-60 Hz
- With door switch connection (optional)

Technical Data

Net width (mm)	483,00
Net height (mm)	25,00
Netto depth (mm)	55,00
Net weight (kg)	0,40

Technical Data - continued

Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	50

Datei Tabelle: Light unit LED, 945lm, Installation on 19", magnet or screwing

Electrical Parameter	
Lamp nominal wattage	7,9 W
Rated voltage/frequency	220-240V AC / 50-60 Hz
Rated current 110-240V AC	0,08 A
Connector door switch	2-pole mini-connector 2,5 A
Connection	2x0,75 mm ² / 1,5 m / wiring color: black
Protection type / -class	
Protection type / -class	IP 20/11
Light bulb	
Typ	18 SMD Power LEDs / 700lm
Life cycle	50.000h
Light colour	white
Norms and certificates	
Labeling	CE
Testing standards	EN 60598
Directives	
Directives	73/23/EWG
More information	
Operating device	-
L x H x W	448 x 54,5 x 26 mm
Weight	approx. 430gr.
Working temperature	-30 to + 60°C
Store temperature	-20 to + 60°C
Humidity at work / Humidity at store	30% / 60%

Article Table

DESCRIPTION	Order No.
Light unit LED, 945lm, Installation on 19", magnet or screwing	DV900336-A
Optional Accessories	
Cable for door switch in DS/DSZ/DSS-enclosures	DV900332
Adapter for DS-, DSZ-, DSS-Enclosure and door switch ACDSW010	DSADA001
Door switch plastic IP65	ACDSW010