


Data Sheet for Article: H5GLY10K0Y

Patchcord RJ45 shielded, Cat.5e, PVC, yellow, 10.0m



SCHRACK Info

Patchcords for generic, structured network cabling systems. Support all applications requiring Class D (e.g. 1000Base-T, 100Base-TX, ATM) as well as VoIP, PoE.

Patchcord with moulded boot in matching cable color. Pin assignment 1:1.

ISO/IEC 11801 2nd ed.; EN 50173-1 and IEC 61156-5.



Technical Data

Category	Cat.5e
Cable construction	4x2xAWG26/7
Cable shielding	SF/UTP
Connection	1:1
Bit rate	up to Gigabit Ethernet
Number of pairs	4
Shielding	shielded
Cable jacket	PVC
LED Functionality	without LED
Net diameter (mm)	5,00

Technical Data - continued

Net weight (kg)	0,33
Colour	Yellow
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	60
RoHS	conform
Patchcordlength (m)	10,0
Net width (mm)	210,00
Net height (mm)	160,00
Connector standard	EN 60603-7
Connector type	RJ45 with 360° shielding
Pin assignment	EIA/TIA 568B 1:1
Packing	Single packed in polybag with label

Article Table

DESCRIPTION	NVP (%)	COPPER WEIGHT (kg/km)	Order No.
Patchcord RJ45 shielded, Cat.5e, PVC, yellow, 10.0m			H5GLY10K0Y
Optional Accessories			
TOOLLESS LINE Jack RJ45 shielded, Cat.5e (SFA)			HSEMRJ5GWS
Patchpanel 19" 24xRJ45 shielded, Cat.5e, 1U, RAL7035 Light grey			HSEMG245GS
F/UTP Cable Cat.5e, 4x2xAWG24/1, PVC, Eca, blue, Box 305m	75	17	HSEKF424P1
F/UTP Cable Cat.5e, 4x2xAWG24/1, LS0H, Eca, blue, Box 305m	75	17	HSEKF424H1
SF/UTP Cable Cat.5e, 4x2xAWG24/1, PVC, Eca, blue Drum 500m	75	23	HSKS424PP5