


Data Sheet for Article: H6GLB10K0B

Patchcord RJ45 shielded, Cat.6, PVC, blue, 10.0m



SCHRACK-Info

Patchcords for generic, structured network cabling systems. Support all applications requiring Class D to Class E (e.g. 1000Base-T, 100Base-TX, ATM) as well as VoIP, PoE.

Patchcord with moulded boot in matching cable color. Pin assignment 1:1.

ISO/IEC 11801 2nd ed.; EN 50173-1 and IEC 61156-6.



Technical Data

Category	Cat.6
Cable construction	4x2xAWG26/7
Cable shielding	S/FTP
Connection	1:1
Bit rate	up to Gigabit Ethernet
Number of pairs	4
Shielding	shielded
Cable jacket	PVC
LED Functionality	without LED
Net weight (kg)	0,32

Technical Data - continued

Colour	Blue
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	60
RoHS	conform
Patchcordlength (m)	10,0
Insulation voltage	300V
Connector standard	EN 60603-7
Connector type	RJ45 with 360° shielding
Pin assignment	EIA/TIA 568B 1:1
Packing	Single packed in polybag with label

Article Table

DESCRIPTION	NVP (%)	COPPER WEIGHT (kg/km)	Order No.
Patchcord RJ45 shielded, Cat.6, PVC, blue, 10.0m			H6GLB10K0B
Optional Accessories			
TOOLLESS LINE Jack RJ45 shielded, Cat.6 (SFA)			HSEMRJ6GWS
TOOLLESS LINE Jack RJ45 shielded, Class Ea 10GB 4PPoE 100W (SFA)			HSEMRJ6GWT
Patchpanel 19" 24xRJ45 shielded, Cat.6, 1U, RAL7035 Light grey			HSEMG246GP
Data Outlet 2xRJ45 shielded Cat.6, UAE, 80x80mm, RAL9010 Pure white, UAE centralplate, Design switch-programme compatible			HSEMG2UW6P
			HSKF423H65
F/FTP Cable Cat.6a, 4x2xAWG23/1, 500MHz, LS0H-3, Dca, blue Sale per meter	79	20	HSEKP423HA
S/FTP Cable Cat.7, 4x2xAWG23/1, 1.000MHz, LS0H, Dca 30% blue Drum 500m	77	25	HSKP423PP5
F/FTP Cable Cat.6a, 2x(4x2xAWG23/1), 500MHz, LS0H-3, Dca blue, Sale per meter	79	40	HSEKP823HA
S/FTP Cable Cat.7, 2x(4x2xAWG23/1), 1.000MHz, LS0H, Dca 30% blue Drum 500m	77	50	HSKP823PP5