

Data Sheet for Article: HSATWT50S-

SAT Mast Bracket Set 50 cm, mast tubes D=38-60 mm, steel

hot-galvanized, two-part



SCHRACK-Info

Hot-dip galvanized steel wall bracket, 2-part, for the securely attaching a mast tube with a diameter of Ø 38 to 60mm to the wall. Wall distance: 150mm, adjustable by 10cm. Mast tube not included.

TECHNICAL DATA

- Material: Quality steel
- Struts : Flat profile 30 x 5mm
- Surface: hot-dip galvanizing approx. 80
- Wall distance: 500mm, adjustable up to 10cm
- twist-proof: with 2x twist-proof claws
- consisting of: 1x bipod and 1x tripod holder
- suitable for mast tubes : Ø 38 to 60mm

Technical Data

Net length (mm)	520,00
Net width (mm)	560,00
Net height (mm)	50,00
Net weight (kg)	3,90
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	60

Article Table

DESCRIPTION	Order No.
SAT Mast Bracket Set 50 cm, mast tubes D=38-60 mm, steel hot-galvanized, two-part	HSATWT50S
Optional Accessories	
SAT Mast, Length=2000mm, DM=50mm, 1.5mm Steel hot-galvanized	HSATMM20S
SAT Mast, Length=2000mm, DM=60mm, 2.0mm Steel hot-galvanized	HSATMM20S6
SAT Mast, Length=3000mm, DM=50mm, 2.0mm Steel hot-galvanized	HSATMM30S
SAT Mast, Length=3000mm, DM=60mm, 2.0mm Steel hot-galvanized	HSATMM30S6