


Data Sheet for Article: HSELS049DR

# FO Splicebox for DIN Rail, 4 Fibers, SC/APC, 9/125µm OS2

RAL7035, incl. Pigtails, incl. couplers, CLASSIC



## Technical Data

|                               |                                |
|-------------------------------|--------------------------------|
| Net width (mm)                | 126,00                         |
| Net height (mm)               | 35,20                          |
| Netto depth (mm)              | 155,65                         |
| Net weight (kg)               | 0,59                           |
| Fiber                         | 9/125 OS2 Singlemode / G.652.D |
| Colour                        | RAL 7035 (Light grey)          |
| Insertion loss typical (dB)   | ≤0,2                           |
| Return loss typical (dB)      | ≥50                            |
| Min. ambient temperature (°C) | -10                            |
| Max. ambient temperature (°C) | 70                             |
| Fibre count                   | 4                              |
| Coupler/Connector             | SC/APC                         |



## Article Table

| DESCRIPTION                                                                                                                                                                                                                                                                                                   | Order No.  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| FO Splicebox for DIN Rail, 4 Fibers, SC/APC, 9/125µm OS2<br>RAL7035, incl. Pigtails, incl. couplers, CLASSIC                                                                                                                                                                                                  | HSELS049DR |
| <b>Optional Accessories</b>                                                                                                                                                                                                                                                                                   |            |
| FO shrink splice protector 60mm                                                                                                                                                                                                                                                                               | HELSP00011 |
| FO shrink splice protector 45mm                                                                                                                                                                                                                                                                               | HELSP00010 |
| Fiber Optics Cleaning Tool for SC, ST, FC and E2000<br>Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.                                                                                                                                                                                  | HSELSZT002 |
| FO Power meter with integrated laser light source (VFL) and<br>RJ45-copper cable test. ATTENTION: This is a Laser Class 2 product. Do not stare into the beam. Always keep the cover on the VFL<br>port when not in use. It is recommended to use laser safety glasses when working with fiber optic systems. | HSELSZT003 |
| FO Patchcord Duplex SC/APC - SC/APC, 9/125µm OS2, 2.0m<br>LSOH, yellow                                                                                                                                                                                                                                        | HLP29DD02F |
| FO Patchcord Duplex SC/APC - SC/APC, 9/125µm OS2, 5.0m<br>LSOH, yellow                                                                                                                                                                                                                                        | HLP29DD05F |
| FO Patchcord Duplex LC/APC - SC/APC, 9/125µm OS2, 2.0m<br>LSOH, yellow                                                                                                                                                                                                                                        | HLP29MD02F |
| FO Patchcord Duplex LC/APC - SC/APC, 9/125µm OS2, 5.0m<br>LSOH, yellow                                                                                                                                                                                                                                        | HLP29MD05F |