

Data Sheet for Article: HSELS089LP

FO Splicebox, 8 Fibers, LC, 9/125µm OS2, 19", 1U, Class C

acc. to IEC 61753-1, RAL7035, sliding, Pigtails included, CLASSIC



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 LC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibres: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Technical Data

Net width (mm)	480,00
Net height (mm)	44,00
Netto depth (mm)	242,00
Net weight (kg)	2,53
Fiber	9/125 OS2 Singlemode / G.652.D
Colour	RAL 7035 (Light grey)
Insertion loss typical (dB)	< 0,2
Return loss typical (dB)	> 50
Min. ambient temperature (°C)	-10
Max. ambient temperature (°C)	70
Fibre count	8

Article Table

DESCRIPTION	Order No.
FO Splicebox, 8 Fibers, LC, 9/125µm OS2, 19", 1U, Class C acc. to IEC 61753-1, RAL7035, sliding, Pigtailed included, CLASSIC	HSELS089LP
Optional Accessories	
FO shrink splice protector 60mm	HELSP00011
FO shrink splice protector 45mm	HELSP00010
Fiber Optics Cleaning Tool for LC and MU Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.	HSELSZT001
FO Power meter with integrated laser light source (VFL) and RJ45-copper cable test. ATTENTION: This is a Laser Class 2 product. Do not stare into the beam. Always keep the cover on the VFL port when not in use. It is recommended to use laser safety glasses when working with fiber optic systems.	HSELSZT003
FO Patchcord Duplex LC/UPC - LC/UPC, 9/125µm OS2, 2.0m LSOH, yellow	HLP29LL02F
FO Patchcord Duplex LC/UPC - LC/UPC, 9/125µm OS2, 5.0m LSOH, yellow	HLP29LL05F

Article Table

DESCRIPTION	Order No.
Optional Accessories	
FO Patchcord Duplex LC/UPC - SC/UPC, 9/125µm OS2, 2.0m LSOH, yellow	HLP29LC02F
FO Patchcord Duplex LC/UPC - SC/UPC, 9/125µm OS2, 5.0m LSOH, yellow	HLP29LC05F
FO Patchcord Duplex LC/UPC - FC/UPC, 9/125µm OS2, 2.0m LSOH, yellow	HLP29LF02F