

Data Sheet for Article: HSELS125LP

FO Splicebox, 12 Fibers, LC, 50/125µm OM2, 19", 1U, Class C

acc. to IEC 61753-1, RAL7035, sliding, Pigtails included, CLASSIC



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 LC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Technical Data

Net width (mm)	480,00
Net height (mm)	44,00
Netto depth (mm)	242,00
Net weight (kg)	2,53
Colour	RAL 7035 (Light grey)
Min. ambient temperature (°C)	-10
Max. ambient temperature (°C)	70
Insertion loss typical (dB)	< 0,2
Return loss typical (dB)	> 35
Fiber	50/125 OM2 Multimode
Fibre count	12

Article Table

DESCRIPTION	Order No.
FO Splicebox, 12 Fibers, LC, 50/125µm OM2, 19", 1U, Class C acc. to IEC 61753-1, RAL7035, sliding, Pigtailed included, CLASSIC	HSELS125LP
Optional Accessories	
FO shrink splice protector 60mm	HELSP00011
FO shrink splice protector 45mm	HELSP00010
FO Patchcord Duplex LC/LC, 50/125µm OM2, LS0H-3, orange, 2.0m	HLP25LL02F
FO Patchcord Duplex LC/LC, 50/125µm OM2, LS0H-3, orange, 5.0m	HLP25LL05F
FO Patchcord Duplex LC/SC, 50/125µm OM2, LS0H-3, orange, 2.0m	HLP25LC02F
FO Patchcord Duplex LC/SC, 50/125µm OM2, LS0H-3, orange, 5.0m	HLP25LC05F
FO Patchcord Duplex LC / ST, 50/125µm OM2, LS0H-3, orange, 2m	HLP25LT02F
FO Patchcord Duplex LC / ST, 50/125µm OM2, LS0H-3, orange, 5m	HLP25LT05F