


Data Sheet for Article: HSELS169DP

FO Splicebox, 16 Fibers, SC/APC, 9/ 125µm OS2, 19", 1U, Class C

acc. to IEC 61753-1, RAL7035, sliding, Pigtails included, CLASSIC



Schrack-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 SC/APC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland

- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
 - Chassis: 1,0mm
 - Sliding tray: 1,25mm
 - Frontpanel: 1,4mm
 - 19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
 - up to 12 fibres: 1 splice-cassette
 - up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Technical Data

Net width (mm)	480,00
Net height (mm)	44,00
Netto depth (mm)	242,00
Net weight (kg)	2,53
Fiber	9/125 OS2 Singlemode / G.652.D
Colour	RAL 7035 (Light grey)
Insertion loss typical (dB)	< 0,2
Return loss typical (dB)	> 50
Min. ambient temperature (°C)	-10
Max. ambient temperature (°C)	70
Fibre count	16

Article Table

DESCRIPTION	Order No.
FO Splicebox, 16 Fibers, SC/APC, 9/125µm OS2, 19", 1U, Class C acc. to IEC 61753-1, RAL7035, sliding, Pigtailed included, CLASSIC	HSELS169DP
Optional Accessories	
FO shrink splice protector 60mm	HELSP00011
FO shrink splice protector 45mm	HELSP00010

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Fiber Optics Cleaning Tool for SC, ST, FC and E2000 Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.	HSELSZT002
FO Power meter with integrated laser light source (VFL) and RJ45-copper cable test. ATTENTION: This is a Laser Class 2 product. Do not stare into the beam. Always keep the cover on the VFL port when not in use. It is recommended to use laser safety glasses when working with fiber optic systems.	HSELSZT003
FO Patchcord Duplex SC/APC - SC/APC, 9/125µm OS2, 1.0m LSOH, yellow	HLP29DD01F
FO Patchcord Duplex LC/APC - SC/APC, 9/125µm OS2, 1.0m LSOH, yellow	HLP29MD01F
FO Patchcord Duplex SC/APC - SC/APC, 9/125µm OS2, 2.0m LSOH, yellow	HLP29DD02F
FO Patchcord Duplex LC/APC - SC/APC, 9/125µm OS2, 2.0m LSOH, yellow	HLP29MD02F
FO Patchcord Duplex SC/APC - SC/APC, 9/125µm OS2, 3.0m LSOH, yellow	HLP29DD03F
FO Patchcord Duplex LC/APC - SC/APC, 9/125µm OS2, 3.0m LSOH, yellow	HLP29MD03F
FO Patchcord Duplex SC/APC - SC/APC, 9/125µm OS2, 5.0m LSOH, yellow	HLP29DD05F
FO Patchcord Duplex LC/APC - SC/APC, 9/125µm OS2, 5.0m LSOH, yellow	HLP29MD05F
FO Patchcord Duplex SC/APC - SC/APC, 9/125µm OS2, 10.0m LSOH, yellow	HLP29DD10F
FO Patchcord Duplex LC/APC - SC/APC, 9/125µm OS2, 10.0m LSOH, yellow	HLP29MD10F