


Data Sheet for Article: HSEUBH165T

FO Universal Cable A/I-DQ(ZN)BH 16x50/125µm OM2, LS0H-3, Dca

nonmetallic rodent protection, black, 8mm, 5000N, Drum 2100m



Technical Data

Fibre count	16
Net diameter (mm)	8,50
Diameter - Central tube (mm)	4
Primary coating (µm)	250 ± 15
Net weight (kg)	0,08
Suitable	Universal cable
Watertightness	Yes
Rodent protection	Yes
Predicted lifetime	> 30 Years
Crush resistance (N/m)	≤ 10000
Cable jacket	LS0H-3
Flame retardancy	Pass
Halogen-free	pH ≥ 3,5 - µS/cm ≤ 100
Smoke Density	Pass

Technical Data - continued

Euroclass acc. to EN50575	Dca
Smoke production	s2
Droplets	d1
Acidity	a1
Temperature range - Transport/storage (°C)	-30 to +70
Temperature range - Installation (°C)	-5 to +50
Temperature range - Operation (°C)	-30 to +70
Pulling tension - Long term (N)	≤ 2500
Pulling tension - Short term (N)	≤ 5000
Bending radii cable - Static (Ø)	10 x Ø
Bending radii cable - Dynamic (Ø)	15 x Ø
Bending radii for fibres and tubes (Ø)	> 25
Mode-Field / Cladding diameter (µm)	50 ± 2,5 125 ± 1
Wavelength (nm)	850 1300
Attenuation (dB/km)	2,3 / 2,8 0,6 / 0,9
Bandwidth (MHz*km)	≥ 600 ≥ 1200
Ehternet performance 1GB (m)	600 600
Ehternet performance 10GB (m)	82 300
Numerical aperture	0,20 ± 0,015
Refractive Index	1,481 1,476

GUIDE TO INSTALLATION AND HANDLING

- When laying and installing optical fibre cables it is vitally important not to exceed the specified values set for pulling tension, bending radii and temperature. The installation methods have to be in accordance with the common standards.
- To ease insertion into tubes by means of compressed air or pulling wire, certified lubricants (e.g. paraffin) may be used.
- The use of soap or similar substances as lubricants is strictly prohibited.
- If a cable needs to be fastened, constrictions > 0.3 mm must be prevented.
- The jelly filling inside the tubes can be removed using a tissue soaked in turpentine.
- It is advisable to cap the cable-ends during storage.

Article Table

DESCRIPTION	Order No.
FO Universal Cable A/I-DQ(ZN)BH 16x50/125µm OM2, LSOH-3, Dca nonmetallic rodent protection, black, 8mm, 5000N, Drum 2100m	HSEUBH165T
Optional Accessories	
FO Splicebox, 16Fibers, LC, 50/125µm OM2, sliding, 19", 1U	HSELS165LG
FO Splicebox, 16Fibers, SC, 50/125µm OM2, sliding, 19", 1U	HSELS165CG
FO Splicebox, 16Fibers, ST, 50/125µm OM2, sliding, 19", 1U	HSELS165TG
FO Splicebox, 16Fibers, FC, 50/125µm OM2, sliding, 19", 1U	HSELS165FG