

Data Sheet for Article: IG009301--

Cable management enclosure Series J, 1 door, size 00

ribbed surface, H=870 W=461 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage



Technical Data

Net width (mm)	461,00
Net height (mm)	870,00
Netto depth (mm)	320,00

Technical Data - continued

Net weight (kg)	14,23
EAN	4029155619758
Power loss (W)	-175, 12
Material	Polyester Glass Fibre Reinforced Plastic
Product category	Cable Management Enclosure
Height (mm)	870
Width (mm)	440
Depth (mm)	320
Number of doors	1
Door type	one door ribbed
Lock	Swinghandle, prepared for Half cylinder
Colour	RAL 7035 (Light grey)
IP Rating	IP44
Protection class	II
Impact Resistance	IK10

Article Table

DESCRIPTION	Order No.
Cable management enclosure Series J, 1 door, size 00 ribbed surface, H=870 W=461 D=320mm, door opening angle 180°	IG009301
Optional Accessories	
Mountingplate for IG009301, H=743 W=410 D=5mm including fastening screws, mounting plate made of melamine-laminated hard paper	IG009331
plastic base frame sizes 00/S3 and 0/S4 600/400 plastic base frame serving as a foundation for plinth	IG790328
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic	IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag	IG790570
foam insert size 00/S3/310 (absorption mat)	IG793816
Plinth Polyester Series J size 00, RAL7035 H=902 W=450 D=310mm	IG009311
Wall mounting kit Size 00-2, for IG0093	IG009300
Ground plate for Wall mounting for IG009301 H=285 W=425 D=4mm	IG009321

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Busbar cover 100mm for 185mm Busbarsystem For mounting on insert nuts M12	ISA05360
Half cylinder lock H36000 with 3 keys, L=40 mm	IL900381