

Data Sheet for Article: IG009303--

Cable management enclosure Series J, 1 door, size 1

ribbed surface, H=870 W=791 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage



Technical Data

Net width (mm)	791,00
Net height (mm)	870,00
Netto depth (mm)	320,00

Technical Data - continued

Net weight (kg)	19,47
EAN	4029155085638
Power loss (W)	-256,54
Material	Polyester Glass Fibre Reinforced Plastic
Product category	Cable Management Enclosure
Height (mm)	870
Width (mm)	785
Depth (mm)	320
Number of doors	1
Door type	one door ribbed
Lock	Swinghandle, prepared for Half cylinder
Colour	RAL 7035 (Light grey)
IP Rating	IP44
Protection class	II
Impact Resistance	IK10

Article Table

DESCRIPTION	Order No.
Cable management enclosure Series J, 1 door, size 1 ribbed surface, H=870 W=791 D=320mm, door opening angle 180°	IG009303
Optional Accessories	
Mountingplate for IG009303, H=743 W=740 D=5mm including fastening screws, mounting plate made of melamine-laminated hard paper	IG009333
plastic base frame sizes 1/S5 800/400 plastic base frame serving as a foundation for plinth	IG790329
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic	IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag	IG790570
foam insert size 1/S5/310 (absorption mat)	IG793819
Plinth Polyester Series J size 1, RAL7035 H=902 W=780 D=310mm	IG009313
Wall mounting kit Size 00-2, for IG0093	IG009300
Ground plate for Wall mounting for IG009303 H=285 W=755 D=4mm	IG009323

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Busbar cover 100mm for 185mm Busbarsystem For mounting on insert nuts M12	ISA05360
Half cylinder lock H36000 with 3 keys, L=40 mm	IL900381