

Data Sheet for Article: IG009401--

Cable management enclosure Series J, dotted, 1 door, size 00

H=1100 W=471 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Technical Data

Net width (mm)	471,00
Net height (mm)	1.100,00

Technical Data - continued

Netto depth (mm)	320,00
Net weight (kg)	22,57
EAN	4029155649922
Power loss (W)	-217,71
Material	Polyester Glass Fibre Reinforced Plastic
Product category	Cable Management Enclosure
Height (mm)	1100
Width (mm)	440
Depth (mm)	320
Number of doors	1
Door type	one door ribbed
Lock	Swinghandle, prepared for Half cylinder
Colour	RAL 7035 (Light grey)
IP Rating	IP44
Protection class	II
Impact Resistance	IK10

Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Cable management enclosure Series J, dotted, 1 door, size 00 H=1100 W=471 D=320mm, door opening angle 180°		IG009401
Optional Accessories		
Mountingplate for IG009401, H=985 W=375 D=5mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009441
plastic base frame sizes 00/S3 and 0/S4 600/400 plastic base frame serving as a foundation for plinth		IG790328
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic		IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag		IG790570
foam insert size 00/S3/310 (absorption mat)		IG793816
Plinth Polyester Series J size 00, RAL7035 H=902 W=450 D=310mm		IG009311
Adapter bar for KVS - IG009401, size 00 (PU= 2 pcs.) Pre-cut with M6 machine tap bit		IG009461

Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Optional Accessories		
Modular chassis 1-21K, 7-rows, complete		IL148121-A
Front plates sheet steel		
self-cutting Lens Head Screw M6 (PU = 4Pieces)		IG009000
for fastening the adapter bars IG900461--, IG009462--, IG009463-- and IG009465--		
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009401 & IG009501		IG009421
H=288 W=429 D=4mm		
Copper busbar Set 4-pole, 30x10mm for Size 00		
For IG009401 and IG009501, 4 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	3400	IG00903100
Copper busbar, 30x10mm for Size 00		
For IG009401 and IG009501, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	1120	IG009P3100
Busbar cover 100mm for 185mm Busbarsystem		ISA05360
For mounting on insert nuts M12		
Half cylinder lock H36000 with 3 keys, L=40 mm		IL900381