

Data Sheet for Article: IG009405--

Cable management enclosure Series J, dotted, 2 doors, size 2

H=1100 W=1130 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Technical Data

Net width (mm)	1.130,00
Net height (mm)	1.100,00

Technical Data - continued

Netto depth (mm)	320,00
Net weight (kg)	42,15
EAN	4029155605294
Power loss (W)	-413,71
Material	Polyester Glass Fibre Reinforced Plastic
Product category	Cable Management Enclosure
Height (mm)	1100
Width (mm)	1115
Depth (mm)	320
Number of doors	2
Door type	two doors ribbed
Lock	Swinghandle, prepared for Half cylinder
Colour	RAL 7035 (Light grey)
IP Rating	IP44
Protection class	II
Impact Resistance	IK10

Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Cable management enclosure Series J, dotted, 2 doors, size 2 H=1100 W=1130 D=320mm, door opening angle 180°		IG009405
Optional Accessories		
Mountingplate for IG009405, H=985 W=1035 D=6mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009445
plastic base frame sizes 2/S6 1200/400 plastic base frame serving as a foundation for plinth		IG790330
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic		IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag		IG790570
foam insert size 2/S6/310 (absorption mat)		IG793820
Plinth Polyester Series J size 2, RAL7035 H=905 W=1110 D=310mm		IG009315
Adapter bar for KVS - IG009405, size 2 (PU=2 pcs.) Pre-cut with M6 machine tap bit		IG009465

Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Optional Accessories		
Modular chassis 4-21K, 7-rows, complete		IL148421-A
Front plates sheet steel		
self-cutting Lens Head Screw M6 (PU = 4Pieces)		IG009000
for fastening the adapter bars IG900461--, IG009462--, IG009463-- and IG009465--		
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009405 & IG009505		IG009425
H=288 W=1088 D=4mm		
Copper busbar Set 4-pole, 30x10mm for Size 2		
For IG009405 and IG009505, 10 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	9610	IG0090312
Copper busbar, 30x10mm for Size 2		
For IG009405 and IG009505, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	2810	IG009P312
Copper busbar, 40x10mm for Size 2		
For IG009405 and IG009505, 10 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	13010	IG0090412
Busbar cover 100mm for 185mm Busbarsystem		ISA05360
For mounting on insert nuts M12		
Half cylinder lock H36000 with 3 keys, L=40 mm		IL900381
Half cylinder lock H36000 with 3 keys, L=40 mm		IL900381