

Data Sheet for Article: IG009502--

Cable management enclosure Series J, 1 door, size 0

dotted surface, H=850 W=605 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Technical Data

Net width (mm)	605,00
Net height (mm)	850,00

Technical Data - continued

Netto depth (mm)	320,00
Net weight (kg)	20,52
IP Rating	IP44
Protection class	II
Impact Resistance	IK10
Material	Polyester Glass Fibre Reinforced Plastic
Colour	RAL 7035 (Light grey)
Width (mm)	605
Height (mm)	850
Depth (mm)	320
Number of doors	1
Lock	Swinghandle, prepared for Half cylinder

Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Cable management enclosure Series J, 1 door, size 0 dotted surface, H=850 W=605 D=320mm, door opening angle 180°		IG009502
Optional Accessories		
Mountingplate for IG009502, H=735 W=500 D=5mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009552
plastic base frame sizes 00/S3 and 0/S4 600/400 plastic base frame serving as a foundation for plinth		IG790328
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic		IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag		IG790570
foam insert size 0/S4/310 (absorption mat)		IG793818
Plinth Polyester Series J size 0, RAL7035 H=902 W=585 D=310mm		IG009312
Ground plate for Wall mounting for IG009302 H=285 W=560 D=4mm		IG009322
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009402 & IG009502 H=288 W=563 D=4mm		IG009422

Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Optional Accessories		
Copper busbar Set 4-pole, 30x10mm for Size 0		
For IG009402 and IG009502, 5 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	4550	IG0090310
Copper busbar, 30x10mm for Size 0		
For IG009402 and IG009502, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	1440	IG009P310
Busbar cover 100mm for 185mm Busbarsystem		ISA05360
For mounting on insert nuts M12		
Half cylinder lock H36000 with 3 keys, L=40 mm		IL900381