

Data Sheet for Article: IG009503--

Cable management enclosure Series J, 1 door, size 1

dotted surface, H=850 W=800 D=320mm, door opening angle 180°



SCHRACK-Info

- Schutzart IP44
- Schutzklasse II
- Schlagfestigkeit IK10
- Türöffnungswinkel 180°
- Wandmontage möglich

Mögliche Ausbauvarianten:

- Leerschrank
- Mit Montageplatte
- Mit Bodenplatte und Wandbefestigungsset zur Wandmontage
- Mit vorgefertigtem Sammelschienensystem



Technical Data

Net width (mm)	800,00
Net height (mm)	850,00

Technical Data - continued

Netto depth (mm)	320,00
Net weight (kg)	24,20
IP Rating	IP44
Protection class	II
Impact Resistance	IK10
Material	Polyester Glass Fibre Reinforced Plastic
Colour	RAL 7035 (Light grey)
Width (mm)	800
Height (mm)	850
Depth (mm)	320
Number of doors	1
Lock	Swinghandle, prepared for Half cylinder

Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Cable management enclosure Series J, 1 door, size 1 dotted surface, H=850 W=800 D=320mm, door opening angle 180°		IG009503
Optional Accessories		
Mountingplate for IG009503, H=735 W=680 D=5mm including fastening screws, mounting plate made of melamine-laminated hard paper		IG009553
plastic base frame sizes 1/S5 800/400 plastic base frame serving as a foundation for plinth		IG790329
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic		IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag		IG790570
foam insert size 1/S5/310 (absorption mat)		IG793819
Plinth Polyester Series J size 1, RAL7035 H=902 W=780 D=310mm		IG009313
Ground plate for Wall mounting for IG009303 H=285 W=755 D=4mm		IG009323
Wall mounting kit Size 00-2, for IG0094 und IG0095		IG009500
Ground plate for Wall mounting for IG009403 & IG009503 H=288 W=758 D=4mm		IG009423

Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Optional Accessories		
Copper busbar Set 4-pole, 30x10mm for Size 1 For IG009403 and IG009503, 7 mounting positions, 100 mm wide, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	6520	IG0090311
Copper busbar, 30x10mm for Size 1 For IG009403 and IG009503, with press-in M12 cage nuts, M12x25 hex bolts and clamping washers	1980	IG009P311
Busbar cover 100mm for 185mm Busbarsystem For mounting on insert nuts M12		ISA05360
Half cylinder lock H36000 with 3 keys, L=40 mm		IL900381