


Data Sheet for Article: IL146442-A

# Metering insert 4-42G compl. 8 cou. pl. front pl. st. Wien

Frontblende Stahlblech, komplett



## Technical Data

|                      |                         |
|----------------------|-------------------------|
| Net width (mm)       | 940,00                  |
| Net height (mm)      | 1.935,00                |
| Netto depth (mm)     | 150,00                  |
| EAN                  | 9004840961782           |
| Product category     | Zählerverteilereinsatz  |
| Austrian province    | Vienna                  |
| Inserts              | front plates sheetsteel |
| Colour               | RAL 7035                |
| Meter width          | 4                       |
| HU                   | 42                      |
| Meter rows           | 2                       |
| Meter slots          | 8                       |
| Downstream rows      | 6                       |
| Front Plate Material | Sheet steel             |
| Basic Description    | Insert                  |
| Module widths        | 270                     |



## Article Table

| DESCRIPTION                                                                                                                                                                                                                                                                                                                                                    | COPPER WEIGHT (kg/km) | Order No.  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------------|
| Metering insert 4-42G compl. 8 cou. pl. front pl. st. Wien<br>Frontblende Stahlblech, komplett                                                                                                                                                                                                                                                                 |                       | IL146442-A |
| <b>Optional Accessories</b>                                                                                                                                                                                                                                                                                                                                    |                       |            |
| Earthing kit 300 mm/Yf6 <sup>2</sup> assembled with all nuts, washer,...                                                                                                                                                                                                                                                                                       |                       | IL900099   |
| Plug-in counter bar 50A for Vienna, Tyrol and Styria<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from coated Copper, RoHS konform, OVE R21:2019                |                       | IL900189   |
| Plug-in counter bar 50A, PU = 64 Pieces<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019                      |                       | IL900189-A |
| Plug-in counter bar pins 63A, 44mm, PU=7 pieces                                                                                                                                                                                                                                                                                                                |                       | IL900190   |
| Cover for Plug-in counter bars                                                                                                                                                                                                                                                                                                                                 |                       | IL900191   |
| Meter Connection Terminal 50A for Czech Republic, wired 1,3m<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019 | 975                   | IL901816   |
| Meter Connection Terminal 50A for Czech Republic, wired 1,8m<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019 | 1350                  | IL901820   |
| Meter Connection Terminal 50A for Czech Republic, wired 2,3m<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019 | 1725                  | IL901824   |