

Data Sheet for Article: IL312312-F

Flush-mounted frame flat + door 3-12, 3-part system, 100mm

1 mm powder coated sheet steel, RAL9016, H=640 W=810 D=100mm



SCHRACK-Info

- Modular designed flush-mounted frame with door
- Material: 1 mm powder coated sheet steel
- Available in sizes from 2U/12 to 3U/24 Modul-high enclosures
- When used with 3-part system wall box IL367xxx-F 100mm deep
- Standard version of door with flush plastic thumbturn operated via integrated double-bit lock
- Protection class: I
- Degree of protection: IP20C
- Impact resistance: IK08
- Color: RAL9016 (Traffic white)



Technical Data

Net width (mm)	810,00
Net height (mm)	640,00
Netto depth (mm)	100,00

Technical Data - continued

Net weight (kg)	5,60
EAN	9004840597585
Power loss (W)	-163,00
Min. ambient temperature (°C)	-5
Max. ambient temperature (°C)	40
Product category	Unterputz Flachverteiler
Colour	RAL 9016 (Traffic White)
Meter width	3
HU	12
IP Rating	IP20C
Basic Description	Frame

Article Table

DESCRIPTION	Order No.
Flush-mounted frame flat + door 3-12, 3-part system, 100mm 1 mm powder coated sheet steel, RAL9016, H=640 W=810 D=100mm	IL312312-F
Optional Accessories	
Wall box 3-12 flat, 3-part system 100mm deep, 132MW 1 mm galvanised sheet steel, H=635 W=800 D=100mm	IL367312-F
Modular chassis 3-12K flat, 4-rows, depth 100 mm Front plates sheet steel, complete	IL148812-A