


Emergency-Stop Main Switch 4-pole, base mounted, 25A

Installation depth (from DIN rail to front panel) for standard shaft length 307 mm For details, see dimension drawing, Version Emergency main switch, Rated current 25A, Poles 4, IP Rating IP54 (front), IP20 (connections)



Technical Data

Version	Emergency main switch
Rated current (A)	25
Poles	4
Mounting	in-ground mounted
Standard	IEC 60947, EN 60947, VDE 0660
Rated insulation voltage [Ui] (V)	690
Rated impulse withstand voltage [Uimp] (V)	6000
Rated short-time withstand current Icw	500
Rated conditional short-circuit-current	10kA @ 440V / 6kA @ 690V
Short-circuit protection maximum fuse	50
Frequency (Hz)	50/60


Technical Data - continued

Operating Current	AC-23A - 400V - 19A AC-3 - 690V - 9.5A AC-23A - 230V - 11A AC-3 - 230V - 15A AC-3 - 400V - 16A AC-22A - 690V - 25A AC-23A - 690V - 11A AC-21A - 690V - 25A
Switching Capacity	AC-3 - 230V - 4kW AC-3 - 400V - 7.5kW AC-23A - 230V - 4kW AC-23A - 400V - 9kW AC-23A - 690V - 9kW AC-3 - 690V - 7.5kW
According to UL 508 / CSA	
Connection type	UL/CSA - AWG 14-6
Operating voltage AC (V)	600
Thermal rated continuous current (A)	25
Active Power	1x240VAC - 3Hp 3x480VAC - 10Hp 1x120VAC - 2Hp 3x120VAC - 3Hp 3x240VAC - 7.5Hp 3x600VAC - 15Hp
Connections	
Conventional thermal current I _{th} (A)	25
Tightening torque (Nm)	3
Connection cross-section, multi-wire (mm ²)	2,5-16
Connection cross section, single wire (mm ²)	2,5-16
Connection cross-section, flexible wire with ferrule (mm ²)	2,5-16
Retrofit contacts	
Auxiliary contacts	Maximum 2x INSHK001 -- permitted. 1x INSHK001 -- can be snapped on to the left side of the main contact and 1x INSHK001 -- to the right side of the main contact. Maximum configuration 2x NC contact / 2x NO contact. The switching behavior is the same regardless of whether the auxiliary contact is snapped on to the left or right side of the main contact.
Neutral conductor contacts	Neutral conductor early-make, late-break design (closes before and opens after the phase conductors to prevent voltage displacement)
Operating temperature	-25°C to +55°C
Mechanical durability	100000 switching cycles
Power loss per pole (W)	0,90
Protection against direct contact	finger-proof and back-of-hand-proof according to VDE 0106 Part 100
IP Rating	IP54 (front), IP20 (connections)


Technical Data - continued

Lockable	With 3 locks, each with a shackle lock diameter of 4-8 mm
Net length (mm)	304,00
Net width (mm)	49,00
Net height (mm)	48,00
Min. ambient temperature (°C)	-25
Max. ambient temperature (°C)	55


Schaltbild INSA2425--




Maßbild INSA2425--



Bohrbild INSA2425--




Montageanleitung INSA Bodeneinbau Schalter



Montageanleitung INSHK Hilfskontakte

Hilfskontakt
Auxiliary contact
INSHK001--



Article Table

DESCRIPTION	Order No.
Emergency-Stop Main Switch 4-pole, base mounted, 25A	
Installation depth (from DIN rail to front panel) for standard shaft length 307 mm For details, see dimension drawing, Version	INSA2425
Emergency main switch, Rated current 25A, Poles 4, IP Rating IP54 (front), IP20 (connections)	
Optional Accessories	
Auxiliary Contact 1NO/1NC for INSR, INSP and INSA	
Nicht für INSE zu verwenden, Version accessories, IP Rating IP20 (terminals)	INSHK001