

Data Sheet for Article: IP3212142-

Feed-through terminal block PT 16 N BU

Push-in connection, cross section: 0.5 mm² - 25 mm², AWG: 20 - 4, width: 12.2 mm, color: blue, NS 35/7.5, NS 35/15



Technical Data

Netto depth (mm)	52,60
Net width (mm)	12,20
Net height (mm)	75,40
Net weight (kg)	0,03
EAN	4046356494830
Power loss (W)	2,43
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	120
Basic Description	Terminal
System	Push-In
Series	PT
Version	Feed-through terminal
Max. cross section, solid wire (mm ²)	25
Max. cross section, flexible wire (mm ²)	16
Max. cross section, flexible wire with ferrule (mm ²)	16
Min. cross section, solid wire (mm ²)	0,50
Min. cross section, flexible wire (mm ²)	0,50

Technical Data - continued

Min. cross section, flexible wire with ferrule (mm ²)	0,50
Cross-section (mm ²)	16
Colour	Blue
Rated current (A)	76

Article Table

DESCRIPTION	Order No.
Feed-through terminal block PT 16 N BU	IP3212142
Push-in connection, cross section: 0.5 mm² - 25 mm², AWG: 20 - 4, width: 12.2 mm, color: blue, NS 35/7.5, NS 35/15	
Optional Accessories	
End bracket CLIPFIX 15, to be snapped onto NS 15 DIN rail	IP3022263
Snap-on end bracket, color: gray	
End bracket CLIPFIX 35-5, for NS 35/7,5 or NS 35/15	IP3022276
Quick mounting end clamp, with marking option, width: 5.15 mm, color: gray	
End bracket CLIPFIX 35, for NS 35/7,5 DIN rail or NS 35/15	IP3022218
Quick mounting end clamp, with marking option, width: 9.5 mm, color: gray	
End bracket E/UK	IP1201442
End clamp, Width: 9.5 mm, Height: 35.3 mm, Length: 50.5 mm, Color: gray	
End bracket E/UK 1	IP1201413
End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray	
End bracket E/MBK	IP1401637
End clamp, width: 6.2 mm, color: gray	
End bracket E/MK 1	IP1421659
End clamp width: 6 mm, color: gray	
End bracket E/NS 35 N	IP0800886
End clamp, width: 9.5 mm, color: gray	
Zack marker strip ZB 12:UNPRINTED	IP0812120
Strip, white, snap into tall marker groove, for terminal width: 12.2 mm, lettering field: 12 x 10.5 mm	
Zack marker strip flat ZBF 12, blank	IP0809735
Strip, white, snap into flat marker groove, for terminal width: 12 mm, lettering field: 5.15 x 12.15 mm	
End cover D-PT 16 N	IP3212060
End cover, length: 75.4 mm, width: 2.2 mm, color: grey	
Plug-in bridge FBS 2-12	IP3005950
Plug-in bridge, pitch: 12 mm, poles: 2, color: red	

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Test plug MPS-MT	IP0201744
Test plug, color: silver	
Insulation sleeve MPS-IH RD	IP0201676
Insulation sleeve, color: red	
Screwdriver 1 x 5.5 (SZF 3-1.0X5.5)	IP1206612
Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip	