


Installation terminal block PTI 4

Push-in connection, cross section: 0.2 mm² - 6 mm², AWG: 24 - 10, width: 6.2 mm, grey, NS 35/7.5, NS 35/15



Technical Data

Netto depth (mm)	42,50
Net width (mm)	6,20
Net height (mm)	66,00
Net weight (kg)	0,01
EAN	4046356609296
Power loss (W)	1,02
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	120
Basic Description	Terminal
System	Push-In
Series	PT
Version	Feed-through terminal
Max. cross section, solid wire (mm ²)	6
Max. cross section, flexible wire (mm ²)	6
Max. cross section, flexible wire with ferrule (mm ²)	4
Min. cross section, solid wire (mm ²)	0,20
Min. cross section, flexible wire (mm ²)	0,20

Technical Data - continued

Min. cross section, flexible wire with ferrule (mm ²)	0,25
Cross-section (mm ²)	6
Colour	Grey
Rated current (A)	32

Article Table

DESCRIPTION	Order No.
Installation terminal block PTI 4	IP3213970
Push-in connection, cross section: 0.2 mm² - 6 mm², AWG: 24 - 10, width: 6.2 mm, grey, NS 35/7.5, NS 35/15	
Optional Accessories	
End bracket CLIPFIX 15, to be snapped onto NS 15 DIN rail	IP3022263
Snap-on end bracket, color: gray	
End bracket CLIPFIX 35-5, for NS 35/7,5 or NS 35/15	IP3022276
Quick mounting end clamp, with marking option, width: 5.15 mm, color: gray	
End bracket CLIPFIX 35, for NS 35/7,5 DIN rail or NS 35/15	IP3022218
Quick mounting end clamp, with marking option, width: 9.5 mm, color: gray	
End bracket E/UK	IP1201442
End clamp, Width: 9.5 mm, Height: 35.3 mm, Length: 50.5 mm, Color: gray	
End bracket E/UK 1	IP1201413
End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray	
End bracket E/MBK	IP1401637
End clamp, width: 6.2 mm, color: gray	
End bracket E/MK 1	IP1421659
End clamp width: 6 mm, color: gray	
End bracket E/NS 35 N	IP0800886
End clamp, width: 9.5 mm, color: gray	
Zack marker strip ZB 6, consecutive numbers 1-10	IP10510161
Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	
Zack marker strip ZB 6, consecutive numbers 11-20	IP10510162
Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	
Zack marker strip ZB 6, consecutive numbers 21-30	IP10510163
Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	
Zack marker strip ZB 6, consecutive numbers 31-40	IP10510164
Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Zack marker strip ZB 6, consecutive numbers 41-50 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510165
Zack marker strip ZB 6, consecutive numbers 51-60 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510166
Zack marker strip ZB 6, consecutive numbers 61-70 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510167
Zack marker strip ZB 6, consecutive numbers 71-80 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510168
Zack marker strip ZB 6, consecutive numbers 81-90 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP10510169
Zack marker strip ZB 6, consecutive numbers 91-100 Strip, white, snap into tall marker groove, for terminal width: 6.2 mm, lettering field: 6.2 x 10.5 mm	IP1051016H
Zack marker strip flat ZBF 6, blank Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP0808710
Zack marker strip flat ZBF 6, consecutive numbers 1-10 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087491
Zack marker strip flat ZBF 6, consecutive numbers 11-20 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087492
Zack marker strip flat ZBF 6, consecutive numbers 21-30 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087493
Zack marker strip flat ZBF 6, consecutive numbers 31-40 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087494
Zack marker strip flat ZBF 6, consecutive numbers 41-50 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087495
Zack marker strip flat ZBF 6, consecutive numbers 51-60 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087496
Zack marker strip flat ZBF 6, consecutive numbers 61-70 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087497
Zack marker strip flat ZBF 6, consecutive numbers 71-80 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087498
Zack marker strip flat ZBF 6, consecutive numbers 81-90 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP08087499
Zack marker strip flat ZBF 6, consecutive numbers 91-100 Strip, white, snap into flat marker groove, for terminal width: 6.2 mm, lettering field: 5.15 x 6.15 mm	IP0808749H
Support bracket AB-PTI Bracket for busbars, set every 20 cm, modular dimensions: 200 x 69.25 mm, 2 mm x 44.8 mm, poles: 1, blue	IP3214006
Plug-in bridge FBS 2-6 Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 10.7 mm, poles: 2, color: red	IP3030336

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Plug-in bridge FBS 3-6	IP3030242
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 16,9 mm, poles: 3, color: red	
Plug-in bridge FBS 4-6	IP3030255
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 23,1 mm, poles: 4, color: red	
Plug-in bridge FBS 5-6	IP3030349
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 29.3 mm, poles: 5, color: red	
Plug-in bridge FBS 10-6	IP3030271
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 60.3 mm, poles: 10, color: red	
Plug-in bridge FBS 20-6	IP3030365
Plug-in bridge, pitch: 6.2 mm, length: 23 mm, width: 122.3 mm, poles: 20, color: red	
Plug-in bridge FBSR 2-6	IP3033715
Plug-in bridge, pitch: 6.2 mm, poles: 2, color: red	
Plug-in bridge FBSR 3-6	IP3001594
Plug-in bridge, pitch: 6.2 mm, poles: 3, color: red	
Plug-in bridge FBSR 4-6	IP3001595
Plug-in bridge, pitch: 6.2 mm, poles: 4, color: red	
Plug-in bridge FBSR 5-6	IP3001596
Plug-in bridge, pitch: 6.2 mm, poles: 5, color: red	
Plug-in bridge FBSR 10-6	IP3033716
Plug-in bridge, pitch: 6.2 mm, poles: 10, color: red	
Screwdriver 0.6 x 3.5 (SZF 1-0.6X3.5)	IP1204517
Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip	