

Data Sheet for Article: IP3270125-

## Potential distributors PTRV 4-PV /BK

250 V, 17.5 A, 0.14 - 2.5, AWG: 14 - 26, pole: 2, Number of connections: 16, 8.3 x 64 mm, grey, elements: black



### Technical Data

|                                                      |               |
|------------------------------------------------------|---------------|
| Netto depth (mm)                                     | 55,50         |
| Net width (mm)                                       | 8,30          |
| Net height (mm)                                      | 64,00         |
| Net weight (kg)                                      | 0,02          |
| EAN                                                  | 4046356943819 |
| Power loss (W)                                       | 0,56          |
| Min. ambient temperature (°C)                        | -40           |
| Max. ambient temperature (°C)                        | 120           |
| Basic Description                                    | Terminal      |
| System                                               | Push-In       |
| Series                                               | PT            |
| Version                                              | accessories   |
| Max. cross section, solid wire (mm²)                 | 2,50          |
| Max. cross section, flexible wire (mm²)              | 1,50          |
| Max. cross section, flexible wire with ferrule (mm²) | 1,50          |
| Min. cross section, solid wire (mm²)                 | 0,14          |
| Min. cross section, flexible wire (mm²)              | 0,14          |

## Technical Data - continued

|                                                                   |       |
|-------------------------------------------------------------------|-------|
| Min. cross section, flexible wire with ferrule (mm <sup>2</sup> ) | 0,14  |
| Cross-section (mm <sup>2</sup> )                                  | 1.5   |
| Colour                                                            | Grey  |
| Rated current (A)                                                 | 17,50 |

| DESCRIPTION                                                                                                                                            | Order No. |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Potential distributors PTRV 4-PV /BK<br>250 V, 17.5 A, 0.14 - 2.5, AWG: 14 - 26, pole: 2, Number of connections: 16, 8.3 x 64 mm, grey,elements: black | IP3270125 |