

Data Sheet for Article: IP3270126-

Potential distributors PTRV 4-PV BU/BK

250 V, 17.5 A, 0.14 - 2.5, AWG: 14 - 26, pole: 2, Number of connections: 16, 8.3 x 64 mm, blue, elements: black



Technical Data

Netto depth (mm)	55,50
Net width (mm)	8,30
Net height (mm)	64,00
Net weight (kg)	0,02
EAN	4046356943826
Power loss (W)	0,56
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	120
Basic Description	Terminal
System	Push-In
Series	PT
Version	accessories
Max. cross section, solid wire (mm²)	2,50
Max. cross section, flexible wire (mm²)	1,50
Max. cross section, flexible wire with ferrule (mm²)	1,50
Min. cross section, solid wire (mm²)	0,14
Min. cross section, flexible wire (mm²)	0,14

Technical Data - continued

Min. cross section, flexible wire with ferrule (mm ²)	0,14
Cross-section (mm ²)	1.5
Colour	Black
Rated current (A)	17,50

DESCRIPTION	Order No.
Potential distributors PTRV 4-PV BU/BK 250 V, 17.5 A, 0.14 - 2.5, AWG: 14 - 26, pole: 2, Number of connections: 16, 8.3 x 64 mm, blue,elements: black	IP3270126