

# TYTAN TH1, D02 Switch disconnecter, 3+N, with monitoring

main protection, with thermal monitoring, with flashing indicator, with fuse plugs, without fuses



## Technical Data

|                               |      |
|-------------------------------|------|
| Power loss (W)                | 7,50 |
| Min. ambient temperature (°C) | -25  |
| Max. ambient temperature (°C) | 60   |
| Poles                         | 3+N  |

## Article Table

| DESCRIPTION                                                                                       | Order No. |
|---------------------------------------------------------------------------------------------------|-----------|
| TYTAN TH1, D02 Switch disconnecter, 3+N, with monitoring                                          | IS503039  |
| main protection, with thermal monitoring, with flashing indicator, with fuse plugs, without fuses |           |
| <b>Optional Accessories</b>                                                                       |           |
| TYTAN HR12 Collective fault message relay 2 C/O, 5A, 250VAC                                       | IS504871  |

## Article Table

| DESCRIPTION                                                     | Order No. |
|-----------------------------------------------------------------|-----------|
| <b>Optional Accessories</b>                                     |           |
| TYTAN HR11 Single fault message relay 2 C/O, 5A, 250VAC         | IS504870  |
| D02-fuse-link 20A, Neozed D02, characteristic gG (gL)<br>blue   | IS504035  |
| D02-fuse-link 25A, Neozed D02, characteristic gG (gL)<br>yellow | IS504036  |
| D02-fuse-link 35A, Neozed D02, characteristic gG (gL)<br>black  | IS504037  |
| D02-fuse-link 50A, Neozed D02, characteristic gG (gL)<br>white  | IS504038  |
| D02-fuse-link 63A, Neozed D02, characteristic gG (gL)<br>copper | IS504039  |
| Adjusting sleeves 20A D02<br>blue                               | IS504134  |
| Adjusting sleeves 25A D02<br>yellow                             | IS504135  |
| Adjusting sleeves 35A D02<br>black                              | IS504136  |
| Adapting D01/D02                                                | ISF90299  |