

Data Sheet for Article: LI1000387-

ANINDA LED 16W, 3000K, 1040lm, 700mA, white matt L-605mm

without driver, wall and ceiling recessed luminaire



Technical Data

Manufacturer	03-SLV
Watt (W)	16
Power (W)	16
Luminous flux (lm)	1040
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Service life	25.000h
Protection class	III
Energy efficiency class	A++ A+ A
Illuminant incl.	yes
System efficiency (lm/W)	65
Operation current mA (mA)	700
Mounting	recessed wall mounting recessed mounting ceiling
Cut-out size (mm)	590x45
Mounting depth (mm)	85
Colour	Black matt

Technical Data - continued

Material	Aluminum Acrylic
Length (mm)	605
Width (mm)	58
Height (mm)	86
Optional Accessories	LI1001133-;LI1001136-;LI464032--
LxWxH mm	605x58x86
Cut-out size mm	590x45

Article Table

DESCRIPTION	Order No.
ANINDA LED 16W, 3000K, 1040lm, 700mA, white matt L-605mm without driver, wall and ceiling recessed luminaire	LI1000387
Optional Accessories	
LED driver, 700mA, 12.5-25W, dimmable	LI1001133
LED driver, 700mA, 12.6-19.6W	LI1001136
TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable inkl. Cable relief	LI464032