

Data Sheet for Article: LI1000388-

ANINDA LED 16W, 3000K, 1040lm, 700mA, silver L-605mm

without driver, wall and ceiling recessed luminaire



Technical Data

Net length (mm)	605,00
Net width (mm)	58,00
Net height (mm)	86,00
Net weight (kg)	1,05
Cut-out size (mm)	590x45
Mounting	recessed wall mounting recessed mounting ceiling
Colour	Silver
Material	Aluminum Acrylic
Manufacturer	03-SLV
Operation current mA (mA)	700
Watt (W)	16
System efficiency (lm/W)	65
Colour temperature (K)	3000
Colour rendering index (Ra)	80
Luminous flux (lm)	1040

Technical Data - continued

Protection class	III
Energy efficiency class	A++ A+ A
Mounting depth (mm)	85
Illuminant incl.	yes
LxWxH mm	605x58x86
Cut-out size mm	590x45

Article Table

DESCRIPTION	Order No.
ANINDA LED 16W, 3000K, 1040lm, 700mA, silver L-605mm without driver, wall and ceiling recessed luminaire	LI1000388
Optional Accessories	
LED driver, 700mA, 12.5-25W, dimmable	LI1001133
LED driver, 700mA, 12.6-19.6W	LI1001136
TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable inkl. Cable relief	LI464032