

Data Sheet for Article: LI1001011 -

# KAMUELA LED, black, 3000K, 38°, IP65

Fire-rated Recessed ceiling luminaire



## Technical Data

|                             |                           |
|-----------------------------|---------------------------|
| Net height (mm)             | 102,00                    |
| Net diameter (mm)           | 88,00                     |
| Net weight (kg)             | 0,27                      |
| Mounting                    | recessed mounting ceiling |
| Colour                      | White                     |
| Material                    | Aluminum                  |
| Manufacturer                | 03-SLV                    |
| Operating voltage AC (V)    | 220-240                   |
| Watt (W)                    | 7,8                       |
| System efficiency (lm/W)    | 77                        |
| Colour temperature (K)      | 3000                      |
| Colour rendering index (Ra) | 80                        |
| Luminous flux (lm)          | 600                       |
| Live time                   | 35.000h                   |
| Protection class            | II                        |
| IP Rating                   | IP65                      |
| Energy efficiency class     | A++   A+   A              |
| Mounting depth (mm)         | 102                       |
| Illuminant incl.            | yes                       |

## Technical Data - continued

|               |        |
|---------------|--------|
| Diameter (mm) | 88     |
| ØxH mm        | 88x102 |

## Article Table

| DESCRIPTION                                                                   | Order No. |
|-------------------------------------------------------------------------------|-----------|
| KAMUELA LED, black, 3000K, 38°, IP65<br>Fire-rated Recessed ceiling luminaire | LI1001011 |