

Data Sheet for Article: LI1005358-

NUMINOS® MOVE S 730lm 250mA 40° 940 black

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

Das NUMINOS Leuchtsystem von SLV vereint Funktion, Design und Technik auf gekonnte Art und Weise. Mit unterschiedlichen Down- und Spotlights erleben Sie Tausend lichtgestalterische Möglichkeiten. Wie mit dem NUMINOS® MOVE S Deckeneinbauleuchte, die durch ihre hochwertige Verarbeitungs- und Lichtqualität besticht. Ideal für eine dezente, moderne und platzsparende Beleuchtung, die den Fokus auf Objekte oder den Raum lenkt. Die Installation gestaltet sich dann im Handumdrehen. Wann entscheiden Sie sich NUMINOS® von SLV?

Technical Data

Luminous flux (lm)	730
Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	40
Power (W)	8,60
Cut-out size (mm)	Ø 90
Length (mm)	100

Technical Data - continued

Width (mm)	100
Height (mm)	63,50
Diameter (mm)	100
LxWxH mm	100x100x64
ØxH mm	100x64
Cut-out size mm	Ø 90

DESCRIPTION	Order No.
NUMINOS® MOVE S 730lm 250mA 40° 940 black Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1005358