

Data Sheet for Article: LI1005371 -

NUMINOS® MOVE S 790lm 250mA 55° 940 white

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

Das NUMINOS Leuchtsystem von SLV vereint Funktion, Design und Technik auf perfekte Art und Weise. Mit unterschiedlichen Down- und Spotlights erleben Sie Tausend lichtgestalterische Möglichkeiten. Dazu gehört auch NUMINOS® MOVE S, die als Deckeneinbauleuchte durch beste Verarbeitungs- und Lichtqualität besticht. So gestalten Sie eine unauffällige, moderne und platzsparende Beleuchtung, die den Fokus auf Objekte oder den Raum lenkt. Die Installation gestaltet sich dann im Handumdrehen. Wann entscheiden Sie sich NUMINOS ® von SLV?

Technical Data

Luminous flux (lm)	790
Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	55
Power (W)	8,60
Cut-out size (mm)	Ø 90
Length (mm)	100

Technical Data - continued

Width (mm)	100
Height (mm)	63,50
Diameter (mm)	100
LxWxH mm	100x100x64
ØxH mm	100x64
Cut-out size mm	Ø 90

DESCRIPTION	Order No.
NUMINOS® MOVE S 790lm 250mA 55° 940 white Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1005371