

Data Sheet for Article: LI1005532-

NUMINOS® XS 690lm 200mA 55° 930/IP44 white/black

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

Design, Technik und Funktion in Perfektion: NUMINOS ist das Leuchtsystem von SLV, das alles vereint. Mit unterschiedlichen Down- und Spotlights erleben Sie Tausend lichtgestalterische Möglichkeiten. Auch mit der NUMINOS® XS Deckeneinbauleuchte, die mit bester Verarbeitungs- und Lichtqualität überzeugt. So gestalten Sie eine dezente, moderne und platzsparende Beleuchtung, die den Fokus auf Objekte oder den Raum lenkt. Die Montage erledigen Sie dann im Handumdrehen. Wann entscheiden Sie sich für die modulare Vielfalt von SLV?

Technical Data

Luminous flux (lm)	690
Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	55
Power (W)	7
Cut-out size (mm)	Ø 55
Length (mm)	65

Technical Data - continued

Width (mm)	65
Height (mm)	45
Diameter (mm)	65
LxWxH mm	65x65x45
ØxH mm	65x45
Cut-out size mm	Ø 55

DESCRIPTION	Order No.
NUMINOS® XS 690lm 200mA 55° 930/IP44 white/black Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1005532