

Data Sheet for Article: LI1005983-

NUMINOS® GIMBLE L 2150lm 700mA 700mA 55° 927 black/chrome

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

Design, Technik und Funktion in Perfektion: NUMINOS ist das Leuchtsystem von SLV, das alles vereint. Die vielfältigen Down- und Spotlights machen Tausend lichtgestalterische Optionen möglich. Auch mit der NUMINOS® GIMBLE L Deckeneinbauleuchte, die mit bester Verarbeitungs- und Lichtqualität überzeugt. Ideal für eine dezente, moderne und platzsparende Beleuchtung, die den Fokus auf Objekte oder den Raum lenkt. Die Installation gestaltet sich dann im Handumdrehen. Wann entscheiden Sie sich NUMINOS ® von SLV?

Technical Data

Luminous flux (lm)	2150
Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	55
Power (W)	25,40
Cut-out size (mm)	Ø 145
Lenght (mm)	160

Technical Data - continued

Width (mm)	160
Height (mm)	115
Diameter (mm)	160
LxWxH mm	160x160x115
ØxH mm	160x115
Cut-out size mm	Ø 145

DESCRIPTION	Order No.
NUMINOS® GIMBLE L 2150lm 700mA 700mA 55° 927 black/chrome Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1005983