

Data Sheet for Article: LI1005985-

NUMINOS® GIMBLE L 2250lm 700mA 20°

927 white

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

Das NUMINOS Leuchtsystem von SLV vereint Technik, Design und Funktionalität wie kein anderes. Mit unterschiedlichen Down- und Spotlights sorgen Sie für Tausend lichtgestalterische Möglichkeiten. Dazu gehört auch NUMINOS® GIMBLE L, die als Deckeneinbauleuchte durch beste Verarbeitungs- und Lichtqualität besticht. Ideal für eine dezente, moderne und platzsparende Beleuchtung, die den Akzent auf Objekte oder den Raum lenkt. Die Montage erledigen Sie dann im Handumdrehen. Wann entscheiden Sie sich für die modulare Vielfalt von SLV?

Technical Data

Luminous flux (lm)	2250
Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	20
Power (W)	25,40
Cut-out size (mm)	Ø 145
Length (mm)	160

Technical Data - continued

Width (mm)	160
Height (mm)	115
Diameter (mm)	160
LxWxH mm	160x160x115
ØxH mm	160x115
Cut-out size mm	Ø 145

DESCRIPTION	Order No.
NUMINOS® GIMBLE L 2250lm 700mA 20° 927 white Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1005985