

Data Sheet for Article: LI1006000-

NUMINOS® GIMBLE L 2300lm 700mA 700mA 55° 930 black/white

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

NUMINOS ist das optimal aufeinander abgestimmte Leuchtsystem von SLV, das Funktion, Design und Technik vereint. Mit unterschiedlichen Down- und Spotlights sorgen Sie für Tausend lichtgestalterische Möglichkeiten. Auch mit der NUMINOS® GIMBLE L Deckeneinbauleuchte, die mit bester Verarbeitungs- und Lichtqualität überzeugt. Ideal für eine dezente, moderne und platzsparende Beleuchtung, die den Akzent auf Objekte oder den Raum lenkt. Die Montage erledigen Sie dann im Handumdrehen. Wann entscheiden Sie sich NUMINOS von SLV – die modulare Vielfalt erwartet Sie.

Technical Data

Luminous flux (lm)	2300
Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	55
Power (W)	25,40
Cut-out size (mm)	Ø 145
Length (mm)	160

Technical Data - continued

Width (mm)	160
Height (mm)	115
Diameter (mm)	160
LxWxH mm	160x160x115
ØxH mm	160x115
Cut-out size mm	Ø 145

DESCRIPTION	Order No.
NUMINOS® GIMBLE L 2300lm 700mA 700mA 55° 930 black/white Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1006000