

Data Sheet for Article: LI1006010-

NUMINOS® GIMBLE L 2200lm 700mA 700mA 55° 930 white/chrome

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

Das NUMINOS Leuchtsystem von SLV vereint Funktion, Design und Technik auf perfekte Art und Weise. Mit vielfältigen Down- und Spotlights erleben Sie Tausend lichtgestalterische Möglichkeiten. Auch mit der NUMINOS® GIMBLE L Deckeneinbauleuchte, die mit bester Verarbeitungs- und Lichtqualität überzeugt. So gestalten Sie eine unauffällige, moderne und platzsparende Beleuchtung, die den Fokus auf Objekte oder den Raum lenkt. Die Installation gestaltet sich dann im Handumdrehen. Wann entscheiden Sie sich NUMINOS von SLV – die modulare Vielfalt erwartet Sie.

Technical Data

Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	55
Power (W)	25,40
Cut-out size (mm)	Ø 145
Length (mm)	160
Width (mm)	160

Technical Data - continued

Height (mm)	115
Diameter (mm)	160
LxWxH mm	160x160x115
ØxH mm	160x115
Cut-out size mm	Ø 145

DESCRIPTION	Order No.
NUMINOS® GIMBLE L 2200lm 700mA 700mA 55° 930 white/chrome Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1006010