

Data Sheet for Article: LI1006018-

NUMINOS® GIMBLE L 2450lm 700mA 700mA 55° 940 black/white

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

Das NUMINOS Leuchtsystem von SLV vereint Technik, Design und Funktionalität wie kein anderes. Mit verschiedenen Down- und Spotlights erleben Sie Tausend lichtgestalterische Möglichkeiten. Dazu gehört auch NUMINOS® GIMBLE L, die als Deckeneinbauleuchte durch beste Verarbeitungs- und Lichtqualität besticht. So gestalten Sie eine dezente, moderne und platzsparende Beleuchtung, die den Fokus auf Objekte oder den Raum lenkt. Die leichte Installation ist dann nur noch Formsache. Wann entscheiden Sie sich NUMINOS von SLV – die modulare Vielfalt erwartet Sie.

Technical Data

Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	55
Power (W)	25,40
Cut-out size (mm)	Ø 145
Length (mm)	160
Width (mm)	160

Technical Data - continued

Height (mm)	115
Diameter (mm)	160
LxWxH mm	160x160x115
ØxH mm	160x115
Cut-out size mm	Ø 145

DESCRIPTION	Order No.
NUMINOS® GIMBLE L 2450lm 700mA 700mA 55° 940 black/white Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1006018