

Data Sheet for Article: LI1006022-

NUMINOS® GIMBLE L 2350lm 700mA 20° 940 white/chrome

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

NUMINOS ist das optimal aufeinander abgestimmte Leuchtsystem von SLV, das Funktion, Design und Technik vereint. So können Sie mit verschiedenen Down- und Spotlights Tausend lichtgestalterische Möglichkeiten erleben. Auch mit der NUMINOS® GIMBLE L Deckeneinbauleuchte, die mit bester Verarbeitungs- und Lichtqualität überzeugt. Ideal für eine dezente, moderne und platzsparende Beleuchtung, die den Akzent auf Objekte oder den Raum lenkt. Die Montage erledigen Sie dann im Handumdrehen. Wann entscheiden Sie sich NUMINOS von SLV – die modulare Vielfalt erwartet Sie.

Technical Data

Luminous flux (lm)	2350
Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	20
Power (W)	25,40
Cut-out size (mm)	Ø 145
Length (mm)	160

Technical Data - continued

Width (mm)	160
Height (mm)	115
Diameter (mm)	160
LxWxH mm	160x160x115
ØxH mm	160x115
Cut-out size mm	Ø 145

DESCRIPTION	Order No.
NUMINOS® GIMBLE L 2350lm 700mA 20° 940 white/chrome Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1006022