

Data Sheet for Article: LI1006023-

NUMINOS® GIMBLE L 2350lm 700mA 40° 940 white/black

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

NUMINOS ist das perfekt aufeinander abgestimmte Leuchtsystem von SLV, das Funktion, Design und Technik vereint. Mit unterschiedlichen Down- und Spotlights erleben Sie Tausend lichtgestalterische Möglichkeiten. Dazu gehört auch NUMINOS® GIMBLE L, die als Deckeneinbauleuchte durch beste Verarbeitungs- und Lichtqualität besticht. So gestalten Sie eine dezente, moderne und platzsparende Beleuchtung, die den Fokus auf Objekte oder den Raum lenkt. Die Installation gestaltet sich dann im Handumdrehen. Wann entscheiden Sie sich NUMINOS® von SLV?

Technical Data

Luminous flux (lm)	2350
Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	40
Power (W)	25,40
Cut-out size (mm)	Ø 145
Length (mm)	160

Technical Data - continued

Width (mm)	160
Height (mm)	115
Diameter (mm)	160
LxWxH mm	160x160x115
ØxH mm	160x115
Cut-out size mm	Ø 145

DESCRIPTION	Order No.
NUMINOS® GIMBLE L 2350lm 700mA 40° 940 white/black Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1006023