

Data Sheet for Article: LI1006024-

NUMINOS® GIMBLE L 2450lm 700mA 40° 940 white

Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!



Product Details

Das NUMINOS Leuchtsystem von SLV vereint Funktion, Design und Technik auf perfekte Art und Weise. Mit verschiedenen Down- und Spotlights erleben Sie Tausend lichtgestalterische Möglichkeiten. Auch mit der NUMINOS® GIMBLE L Deckeneinbauleuchte, die mit bester Verarbeitungs- und Lichtqualität überzeugt. So gestalten Sie eine unauffällige, moderne und platzsparende Beleuchtung, die den Fokus auf Objekte oder den Raum lenkt. Die Montage erledigen Sie dann im Handumdrehen. Wann entscheiden Sie sich NUMINOS ® von SLV?

Technical Data

Luminous flux (lm)	2450
Dimmable	Depending on driver yes
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	40
Power (W)	25,40
Cut-out size (mm)	Ø 145
Length (mm)	160

Technical Data - continued

Width (mm)	160
Height (mm)	115
Diameter (mm)	160
LxWxH mm	160x160x115
ØxH mm	160x115
Cut-out size mm	Ø 145

DESCRIPTION	Order No.
NUMINOS® GIMBLE L 2450lm 700mA 40° 940 white Recessed ceiling luminaire, cardanic rotating and pivoting, Note: LED driver must be ordered separately!	LI1006024