

Data Sheet for Article: LI1009226-

# EASYLIGHT 2500 140 830/840/850 DA30 ML DALI2 Trunking System



## Technical Data

|                             |                                           |
|-----------------------------|-------------------------------------------|
| Net length (mm)             | 2.500,00                                  |
| Net width (mm)              | 65,00                                     |
| Net height (mm)             | 68,00                                     |
| Net weight (kg)             | 3,69                                      |
| Colour                      | White                                     |
| Material                    | Aluminum<br>PMMA                          |
| Operating voltage AC (V)    | 220-240                                   |
| Lamp holder                 | LED Platine                               |
| System efficiency (lm/W)    | 171,23                                    |
| Power (W)                   | 80                                        |
| Light colour                | neutral white<br>warm white<br>cool white |
| Colour temperature (K)      | 5000<br>4000<br>3000                      |
| Colour rendering index (Ra) | 80                                        |

## Technical Data - continued

|                    |                       |
|--------------------|-----------------------|
| Luminous flux (lm) | 12500 / 14000 / 14000 |
| Service life       | 100000                |
| Dimmable           | DALI                  |
| Protection class   | I                     |
| Shock strength     | IK06                  |
| LxWxH mm           | 2500x65x68            |

| DESCRIPTION                                                  | Order No. |
|--------------------------------------------------------------|-----------|
| EASYLIGHT 2500 140 830/840/850 DA30 ML DALI2 Trunking System | LI1009226 |