

Data Sheet for Article: LI111101NW

LED Panel Square 100 6W, 4000K, 420lm, Ra>80, dimm, white



Technical Data

Net length (mm)	115,00
Net width (mm)	115,00
Net height (mm)	13,00
Net weight (kg)	0,32
Cut-out size (mm)	105x100
Luminaire type	LED Panel
Mounting	recessed wall mounting recessed mounting ceiling
Colour	RAL 9016 (white)
Material	Aluminum
Manufacturer	O2-Schrack
Emission angle (°)	120
Controller	LED driver
Operating voltage AC (V)	230
Light source	LED
Lamp holder	LED Platine
Watt (W)	6
System efficiency (lm/W)	70

Technical Data - continued

Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	420
Number of lamps	1
Live time	30.000h
Dimmable	TRIAC
Protection class	III
IP Rating	IP20
Illuminant incl.	yes
LxWxH mm	115x115x13
Cut-out size mm	105x100

Article Table

DESCRIPTION	Order No.
LED Panel Square 100 6W, 4000K, 420lm, Ra>80, dimm, white	L1111101NW
Optional Accessories	
3-way connection box, IP20, Quick Fix	LID15379