

Data Sheet for Article: LI111290--

FRAME CURVE LED, 1W, neutralwhite, square, silvergrey



Technical Data

Optional Accessories	LI111850--,LI111860--,LI111861--,LI111862--,LI112780--,LI112781--,LI464107--
Luminaire type	Recessed wall luminaire
Mounting	recessed wall mounting
Colour	Silver grey
Material	Aluminum
Manufacturer	O3-SLV
Controller	LED driver
Light source	LED
Watt (W)	1
System efficiency (lm/W)	110
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	110
Number of lamps	1
Service life	30.000h
Protection class	III

Technical Data - continued

Mounting depth (mm)	45
Illuminant incl.	yes
Power (W)	1

Article Table

DESCRIPTION	Order No.
FRAME CURVE LED, 1W, neutralwhite, square, silvergrey	LI111290
Optional Accessories	
Plug connector x3 with two bridges for LED, max. 350mA	LI111850
Connector set for LED article x6 with three bridges	LI111860
Cable extension for items with a 350mA plug, 1 m	LI111861
Cable extension for articles with 350mA connector, 2m	LI111862
Flush-mounted frame for FLAT FRAME and BASIC LED series	LI112780
Installation box for FLAT FRAME and FRAME BASIC LED	LI112781
LED-DRIVER, 3VA, 350mA, with AMP plug, incl. stress relief	LI464107