


Data Sheet for Article: LI114410--

NEW TRIA MINI DL SQUARE, 3W, 3000K, 30°, matt black

incl. MI-Plug & clip spring



Technical Data

Cut-out size (mm)	Ø40
Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	Black
Material	Aluminum
Emission angle (°)	30
Light source	LED
Watt (W)	2,20
System efficiency (lm/W)	65
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	143
Number of lamps	1
Live time (h)	30000
Protection class	III
IP Rating	IP44

Technical Data - continued

Mounting depth (mm)	40
Illuminant incl.	yes
LxWxH mm	52x52x36
Cut-out size mm	Ø40

Article Table

DESCRIPTION	Order No.
NEW TRIA MINI DL SQUARE, 3W, 3000K, 30°, matt black incl. MI-Plug & clip spring	LI114410
Optional Accessories	
LED-Driver 11 W, 700mA, incl. strain relief	LI464030
Plugbar, 3 Exit with 2 Bridges, max. 700mA, black	LI111830
Plugbar, 6 Exit with 3 Bridges, max. 700mA, black	LI111831
cable extension for Article with 700mA, 1m	LI111832