

Data Sheet for Article: LI115193--

COB LED MODUL for AIXLIGHT PRO mounting frame, 30°, silvergr



Technical Data

Manufacturer	03-SLV
Luminous flux (lm)	3200
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Service life	30.000h
Protection class	III
Energy efficiency class	A++ A+ A
Luminaire type	Recessed ceiling luminaire
Light source	COB LED
Illuminant incl.	yes
Number of lamps	1
System efficiency (lm/W)	91
Power (W)	35
Operating voltage AC (V)	230
Mounting	recessed mounting ceiling
Colour	Silver grey

Technical Data - continued

Material	Aluminum Glass
Optional Accessories	LI1001267-, LI115600--, LI464032--, LI464168--, LI464170--, LI464174-- , LI464176--
ØxH mm	135x130

Article Table

DESCRIPTION	Order No.
COB LED MODUL for AIXLIGHT PRO mounting frame, 30°, silvergr	LI115193
Optional Accessories	
LED Driver 36W, 700mA, dimmable	LI1001267
AIXLIGHT PRO ZIERRING, aluminium, white	LI115600
TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dimmable inkl. Cable relief	LI464032
LED-Driver, 40W, 700mA, incl. strain relief	LI464168
LED-Driver, 40W, 1000mA, incl. strain relief	LI464170
LED-Driver, 40W, 700mA, incl. strain relief, dimmable	LI464174
LED-Driver, 40W, 1000mA, incl. strain relief, dimmable	LI464176